



# FlashPure TLC Plates

## Technical data sheet



Item Number	Description	Coated material				Backing	Plate dimension	Fluorescent indicator
		Phase	Particle size	Pore volume	Specific surface area			
148621250	FlashPure ID TLC Plates Silica Glass backed (UV 254nm) 20 x 20cm, 25 pcs	Silica	5-17µm	0.74-0.76mL/g	350-450m <sup>2</sup> /g	Glass	20 x 20cm	yes (UV 254nm)
148628490	FlashPure ID TLC Plates Silica Aluminum backed (UV 254nm) 20 x 20cm, 25 pcs	Silica	5-17µm	0.74-0.76mL/g	350-450m <sup>2</sup> /g	Aluminum	20 x 20cm	yes (UV 254nm)
140000174	FlashPure EcoFlex TLC Plates Silica Glass backed (UV 254nm) 20 x 20cm, 20 pcs	Silica	6-10µm	0.8-1.0mL/g	300-400m <sup>2</sup> /g	Glass	20 x 20cm	yes (UV 254nm)
140000175	FlashPure EcoFlex TLC Plates Silica Aluminum backed (UV 254nm) 20 x 20cm, 20 pcs	Silica	6-10µm	0.8-1.0mL/g	300-400m <sup>2</sup> /g	Aluminum	20 x 20cm	yes (UV 254nm)
140000179	FlashPure EcoFlex TLC Plates Alumina Neutral Glass backed (UV 254nm) 20 x 20cm, 20 pcs	Alumina neutral	< 48µm	0.05-0.10mL/g	50-100m <sup>2</sup> /g	Glass	20 x 20cm	yes (UV 254nm)